






PRODUCT HIGHLIGHTS

- Ideal retrofit solution for a vast range of spots and downlights
- Fitted with the latest LED technology
- LED replacement for 50W halogen MR16 lamps
- Up to 80% energy saving compared to a standard halogen reflector lamp
- Long service lifetime of 16'000 hours
- No UV or IR emissions
- Recommended for public areas such as receptions, lobbies, corridors...
- Certified: CE / ERP / RoHS

C GENERAL CHARACTERISTICS

Product Reference	L
Shape	Ν
Base	C
Dimmable	Ν
Energy Efficiency Label	A
Materials Housing	Т
Diffuser	P
LED Type	S
LED Quantity	6
Service Lifetime	1
Start Time from 0% to 100%	С
Mercury Content	С
Ingress Protection	
Dimensions (d x h)	Q

LD MR16 G8 5.5W/230V/WFL/830/GU5.3 MR16 GU5.3 No A+ Thermo-plastic Plastic optic smooth lens SMD 2835 6 16'000 hours 0 sec 0.0 mg IP20 Ø 50 x 45 mm




ELECTRICAL CHARACTERISTICS

Rated Power	5.5W
Operating Frequency	50-60 Hz
Input Voltage	220-240V AC
Power Factor	0.5



Luminous Flux	400 lm
Luminous Intensity	1′000 cd
Beam Angle	38°
Colour Name	Warm White
Colour Temperature (CCT)	3'000 K
CRI	> 80



~ Creo Light is a Registered Trademark ~ Subject To Change Without Prior Notice. Version 21.08