






PRODUCT HIGHLIGHTS

- Ideal retrofit solution for a vast range of spots and downlights
- Fitted with the latest LED technology
- LED replacement for 50W halogen MR16 lamps
- Up to 80% energy ~ saving compared to a standard halogen reflector lamp
- Long service lifetime of 15'000 hours
- No UV or IR emissions
- Recommended for public areas such as receptions, lobbies, corridors...
- Certified: CE / ERP / RoHS

C GENERAL CHARACTERISTICS

Product Reference Shape Base Dimmable Energy Efficiency Label Materials Housing Diffuser LED Type LED Quantity Service Lifetime Start Time from 0% to 100% 0 sec Mercury Content Ingress Protection Dimensions (d x h)

LD MR16 G6 6.1W/12V/WFL/830/GU5.3/DIM **MR16** GU5.3 Yes A+ Thermo-plastic Plastic optic smooth lens SEOUL™ 10 15'000 hours 0.0 mg IP20 Ø 50 x 45 mm



-Č

ELECTRICAL CHARACTERISTICS

Rated Power	6.1W
Operating Frequency	50-60 Hz
Input Voltage	12V AC/DC*
Power Factor	0.5

)-	LIGHT	CHARA	CTERISTICS	
	Luminou	e Elux	621	

Luminous Flux	621 lm
Luminous Intensity	1′100 cd
Beam Angle	36°
Colour Name	Warm White
Colour Temperature (CCT)	3'000 K
CRI	> 80

*Warning: Warranty is valid for compatible ET & Dimmers. List available upon request.

