





PRODUCT HIGHLIGHTS

- Ideal retrofit solution for a vast range of spots and downlights
- Fitted with the latest LED technology
- LED replacement for 70W halogen PAR16 lamps
- Up to 80% energy saving compared to a standard halogen reflector lamp
- Long service lifetime of 15'000 hours
- No UV or IR emissions
- Recommended for public areas such as receptions, lobbies, corridors
- Certified: CE / ERP / RoHS

GENERAL CHARACTERISTICS

| Product Reference | | L |
|-------------------------|----------|---|
| Shape | | F |
| Base | | C |
| Dimmable | | Υ |
| Energy Efficiency Label | | A |
| Materials | Housing | Т |
| | Diffuser | F |
| LED Type | | E |
| LED Quantity | | 8 |
| Service Lifetime | | 1 |
| Start Time from 0% | to 100% | С |
| Mercury Content | | С |
| Ingress Protection | | |
| Dimensions (d x h) | | Q |
| | | |


LD PAR16 G6 7W/230V/WFL/830/GU10/DIM PAR16 GU10 Yes A+ Thermo-plastic Plastic optic smooth lens BRIDGELUX™ 8 15'000 hours 0 sec 0.0 mg IP20 Ø 50 x 54 mm



ELECTRICAL CHARACTERISTICS

| Rated Power | 7W |
|---------------------|----------|
| Operating Frequency | 50-60 Hz |
| Input Voltage | 220-240V |
| Power Factor | 0.7 |

| Luminous Flux | 500 lm |
|--------------------------|------------|
| Luminous Intensity | 950 cd |
| Beam Angle | 36° |
| Colour Name | Warm White |
| Colour Temperature (CCT) | 3′000 K |
| CRI | > 80 |
| | |



~ Creo Light is a Registered Trademark ~ Subject To Change Without Prior Notice. Version 21.11