

LED T5




## PRODUCT HIGHLIGHTS

- ~ Ideal retrofit solution for fluorescent lamps
- ~ Operates without ballast (100-240V). Instant start
- ~ Uniform light distribution & high luminous output
- ~ No RF interference. No flickering or buzzing
- ~ Recommended for public areas such as parkings, warehouses, corridors ...etc.
- ~ Long service lifetime of 30'000 hours
- ~ No UV or IR emissions. No mercury

## GENERAL CHARACTERISTICS

Product Name	LD T5
Energy Efficiency Label	A
Materials:	Housing PC Reflector PC
LED Brand	EPISTAR™
LED Type	3528
Service Lifetime	30'000 hours
Ingress Protection	IP20



## ELECTRICAL & PHOTOMETRIC CHARACTERISTICS

Product reference	RATED POWER	INPUT VOLTAGE AC	OPERATING FREQUENCY	POWER FACTOR	BEAM ANGLE	CCT	CRI	LUMINOUS FLUX (lm)	LUMINOUS EFFICIENCY (lm/W)	WIDTH (d) (mm)	LENGTH (L) (mm)
LD T5 8W/230V/WW/G5	8W	100-240V	50-60 Hz	0.6	120°	3'000 K	> 80	800	100	Ø 16	550
LD T5 8W/230V/NW/G5	8W	100-240V	50-60 Hz	0.6	120°	4'000 K	> 80	800	100	Ø 16	550
LD T5 16W/230V/WW/G5	16W	100-240V	50-60 Hz	0.6	120°	3'000 K	> 80	1'600	100	Ø 16	1'150
LD T5 16W/230V/NW/G5	16W	100-240V	50-60 Hz	0.6	120°	4'000 K	> 80	1'600	100	Ø 16	1'150