

LED Slim Converter 100W 24V IP67

PRODUCT HIGHLIGHTS

- Constant voltage LED slim waterproof driver
- Output voltage 24V
- Built-in protections: Overload - Over voltage - Short circuit - Over temperature
- 100% full load burn-in test
- Suitable for LED lighting
 - Certified: CE / RoHS

Metal casing

Long service lifetime of 50'000 hours

GENERAL CHARACTERISTICS


LED Slim Converter 100W 24V IP67 Product Name Dimensions (I x w x h) 270 x 61 x 25 mm

Weight 820 g Ingress Protection IP67

Working Temp. -20°C...+60°C,

Storage Temp. & Humid. -40°C...+85°C, 20...90% RH

Service Lifetime 50'000 hours





ELECTRICAL CHARACTERISTICS

Product Reference	CVS24100M67
Rated Power	100W
Output Voltage	24V DC
Output Rated Current	4.17A
Ripple & Noise (max)	< 350mVp-p
Input Voltage	100-240V AC
Main Frequency	47-63 Hz
AC Current	1.3A max @240V AC (full load)
Inrush Current	Cold Start < 50A @220V AC (full load)
Number of Output Channel	1
Output Voltage Tolerance	±2%
Setup, Rise Time (max)	< 1s/220V AC at full load
Short Circuit	Recovers automatically after fault condition is removed
Over Voltage	< 36VDC Shut down the output, After restart recovers automatically
Over Current	< 5.5A auto recovery when failure is removed