

LED Slim Converter 200W 12/24V IP20

## PRODUCT HIGHLIGHTS

- Constant voltage LED slim driver
- Output voltage 12 or 24V
- Built-in protections:
  Overload Over
  voltage Short circuit
  Over temperature
- ➤ 100% full load burn-in test
- Suitable for LED lighting
- Certified: CE / RoHS

Metal casing

 Long service lifetime of 26'000 hours

## 4

## **GENERAL CHARACTERISTICS**

Product Name LED Slim Converter 200W 12/24V IP20


Dimensions (l x w x h)  $307 \times 53 \times 21.5 \text{ mm}$ 

Weight 335 g Ingress Protection IP20

Working Temp. -20°C...+60°C,

Storage Temp. & Humid. -40°C...+85°C, 20...90% RH

Service Lifetime 26'000 hours





## **ELECTRICAL CHARACTERISTICS**

Product Reference	CVS12200M20	CVS24200M20
Rated Power	200W	200W
Output Voltage	12V DC	24V DC
Output Rated Current	16.6A	8.33A
Ripple & Noise (max)	< 350mVp-p	< 350mVp-p
Input Voltage	200-240V AC	
Main Frequency	47-63 Hz	
AC Current	2.6A max @220V AC (full load)	
Inrush Current	Cold Start < 50A @220V AC (full load)	
Number of Output Channel	2	
Output Voltage Tolerance	±4%	±2%
Setup, Rise Time (max)	< 1s/220V AC at full load	
Short Circuit	Recovers automatically after fault condition is removed	
Over Voltage	< 18V DC Shut down the output,	< 36VDC Shut down the output, After
	After restart recovers automatically	restart recovers automatically
Over Current	< 21A auto recovery when failure is	< 11A auto recovery when failure is
	removed	removed