

LED Slim Converter 240W 24V IP67



PRODUCT HIGHLIGHTS

- Constant voltage LED slim waterproof driver
- Output voltage 24V
- Built-in protections: Overload - Over voltage - Short circuit - Over temperature
- 100% full load burn-in test
- Suitable for LED lighting
 - Long service lifetime of 50'000 hours
- Metal casing
- Certified: CE / RoHS

GENERAL CHARACTERISTICS

LED Slim Converter 240W 24V IP67 Product Name Dimensions (I x w x h) 270 x 68 x 30 mm

1′055 g Weight Ingress Protection IP67

Working Temp. -20°C...+60°C,

Storage Temp. & Humid. -40°C...+85°C, 20...90% RH

Service Lifetime 50'000 hours





ELECTRICAL CHARACTERISTICS

Product Reference	CVS24240M67
Rated Power	240W
Output Voltage	24V DC
Output Rated Current	10A
Ripple & Noise (max)	< 240mVp-p
Input Voltage	100-240V AC
Main Frequency	47-63 Hz
AC Current	3.2A max @230V AC (full load)
Inrush Current	Cold Start < 50A @230V AC (full load)
Number of Output Channel	1
Output Voltage Tolerance	±5%
Setup, Rise Time (max)	< 1s/230V AC at full load
Short Circuit	Recovers automatically after fault condition is removed
Over Voltage	< 28VDC Shut down the output, After restart recovers automatically
Over Current	< 13A auto recovery when failure is removed