



**Spot SPX06  
6W 230V WW IP42**



## PRODUCT HIGHLIGHTS

- LED Spot SPX06 with consistent colour temperature
- Operates with remote constant current LED driver
- Long service lifetime of 50'000 hours
- Simple recessed installation suitable for various ceiling thickness (from 1 mm and above)
- Uniform light distribution
- No UV or IR emissions. No mercury
- Excellent Colour Rendering (CRI > 90)
- 2'700 K and 4'000 K versions available upon request
- Available in white or black

## GENERAL CHARACTERISTICS

Product Name	Spot SPX06 6W 230V WW IP42	
Energy Efficiency Label	A	
Materials	Body	Aluminium
LED Brand	OSRAM™	
LED Type	COB	
LED Quantity	1 Module	
Average Lifetime	50'000 hours	
Start Time from 0% to 100%	0 sec	
Mercury Content	0.0 mg	
Ingress Protection	IP42	
Dimensions (d x h)	Ø 88 x 50 mm	
Cut-Out	Ø 75 mm	



## ELECTRICAL CHARACTERISTICS

System Power	6W
Input Voltage	230V AC
Forward Voltage	36V DC
Forward Current	150 mA
Power Factor	0.9



## LIGHT CHARACTERISTICS

Product Reference	SPX06FL93042	SPX06WF93042	SPX06VW93042
Beam Angle	24°	36°	50°
Colour Name	Warm White	Warm White	Warm White
Colour Temperature (CCT)	3'000 K	3'000 K	3'000 K
CRI	> 90	>90	>90