



**Track Light
TL0612 IP20**




PRODUCT HIGHLIGHTS

- High quality LED Track Light providing symmetric light distribution with maximum efficiency and optimum photometric properties
- Compatible with EU standard tracks from Global, Stucchi
- Standard CCT: 3'000 K and 4'000 K (Optional 2'700K and 5'000K)
- High system efficiency up to 120 lm/W and total luminous flux up to 2'400 lm
- Integrated in-track driver with fixed output, DALI and Bluetooth dimming
- Different beam angle available
- Excellent Colour Rendering Index CRI > 90 (Optional 80)
- Long service lifetime of 50'000 hours
- Available in white, black or silver

GENERAL CHARACTERISTICS

Product Name	TL0612
Energy Efficiency Label/Reel	A+
Materials:	Housing Aluminium Reflector Aluminium
LED Type	COB
LED Quantity	1 Module
Service Lifetime	50'000 hours
Ingress Protection	IP20



ELECTRICAL & PHOTOMETRIC CHARACTERISTICS

Product reference	RATED POWER	INPUT VOLTAGE	OPERATING FREQUENCY	BEAM ANGLE	CCT	CRI	LUMINOUS FLUX (lm)	LUMINOUS INTENSITY (cd)	DIAMETER (d) (mm)	HEIGHT (h) (mm)	WIDTH (w) (mm)
TL0612SP930	20 W	220-240V	50-60 Hz	16°	3'000 K	> 90	2'400	6'223	Ø 60	127	153
TL0612FL930	20 W	220-240V	50-60 Hz	26°	3'000 K	> 90	2'400	3'543	Ø 60	127	153
TL0612WF930	20 W	220-240V	50-60 Hz	36°	3'000 K	> 90	2'400	2'330	Ø 60	127	153
TL0612SP940	20 W	220-240V	50-60 Hz	16°	4'000 K	> 90	2'400	6'223	Ø 60	127	153
TL0612FL940	20 W	220-240V	50-60 Hz	26°	4'000 K	> 90	2'400	3'543	Ø 60	127	153
TL0612WF940	20 W	220-240V	50-60 Hz	36°	4'000 K	> 90	2'400	2'330	Ø 60	127	153