



**LED Wall Fixture  
Cylinder WFC IP65**




## PRODUCT HIGHLIGHTS

- LED wall cylindrical fixture
- Simple wall mounting installation
- Built-in fixed output LED driver included
- Dimmable LED driver available upon request
- Symmetric light distribution with optimum photometric properties
- High colour consistency and excellent CRI (CRI > 80)
- Available in black or white
- Long service lifetime of 50'000 hours

## GENERAL CHARACTERISTICS

Product Name	LED Wall Fixture Cylinder WFC IP65
Energy Efficiency Label	A+
Materials	Housing Aluminium
LED Type	COB
Service Lifetime	50'000 hours
Power Factor	0.9
Ingress Protection	IP65
Temperature Range	-20° ... +50°C
Operating Frequency	50-60 Hz
Input Voltage	100-240V AC



## ELECTRICAL & PHOTOMETRIC CHARACTERISTICS

Product Reference	RATED POWER	BEAM ANGLE	LUMINOUS FLUX (lm)	LUMINOUS EFFICIENCY (lm/W)	CCT	CRI	DIAMETER (d) (mm)	HEIGHT (h) (mm)	WIDTH (w) (mm)	WEIGHT (g)
WFC0617SP830	10 W	15°	700	70	3'000K	> 80	Ø 60	170	105	600
WFC0617FL830	10 W	24°	700	70	3'000K	> 80	Ø 60	170	105	600
WFC0617WF830	10 W	60°	700	70	3'000K	> 80	Ø 60	170	105	600
WFC0720SP830	20 W	15°	2'000	100	3'000K	> 80	Ø 76	200	121	900
WFC0720WF830	20 W	36°	2'000	100	3'000K	> 80	Ø 76	200	121	900
WFC0720VW830	20 W	60°	2'000	100	3'000K	> 80	Ø 76	200	121	900
WFC1023SP830	27 W	15°	2'800	104	3'000K	> 80	Ø 100	230	145	1'200
WFC1023WF830	27 W	24°	2'800	104	3'000K	> 80	Ø 100	230	145	1'200
WFC1023VW830	27 W	60°	2'800	104	3'000K	> 80	Ø 100	230	145	1'200