

**Architectural Serie  
Recessed Step Light  
ASST0402  
2W 700mA WW IP65**




## PRODUCT HIGHLIGHTS

- ~ Recessed LED Step Light from the Architectural Serie with consistent colour temperature
- ~ High brightness LED light with consistent colour temperature
- ~ Uniform light distribution
- ~ Simple recessed installation
- ~ Excellent Colour Rendering (CRI>85)
- ~ Operates with 700 mA constant current LED driver (driver included)
- ~ Long service lifetime of 25'000 hours
- ~ 2'700 K and 4'000 K versions available upon request
- ~ No UV or IR emissions. No mercury



## GENERAL CHARACTERISTICS

Product Name	Architectural Serie Recessed Step Light ASST0402 2W 700mA WW IP65
Energy Efficiency Label	A
Materials	Body Anodized Aluminium
LED Type	COB
LED Quantity	1
Average Lifetime	25'000 hours
Start Time from 0% to 100%	0 sec
Mercury Content	0.0 mg
Ingress Protection	IP65
Dimensions (d x h)	Ø 44 x 27 mm
Cut-Out	Ø 36 mm



## ELECTRICAL CHARACTERISTICS

System Power	2W
Forward Voltage	3V DC
Forward Current	700mA



## LIGHT CHARACTERISTICS

Product Reference	AAST0402830
Luminous Flux	90 lm
Luminous Intensity	-
Luminous Efficiency	45 lm/W
Beam Angle	-
Colour Name	Warm White
Colour Temperature (CCT)	3'000 K
CRI	>85