



**Ceiling Surface Mounted Fixture CLSM2818 3CCT IP65**




## PRODUCT HIGHLIGHTS

- ~ Surface Mounted Ceiling LED fixture for damp environments and covered exterior areas
- ~ Chemically resistant against alcohol, ethanol and hydrogen peroxide
- ~ Integrated slide switch 3 in 1. Possibility to choose between 3'000K, 4'000K or 6'500K
- ~ High luminous efficacy up to 83 lm/w
- ~ Areas of application: Indoor and outdoor locations, Industrial and storage facilities, Car parks and underpasses, Garages, Workshops and assembly lines
- ~ 3 years guarantee

## GENERAL CHARACTERISTICS

Product Name	LED Ceiling Surface Mounted Fixture CLSM2818 3CCT IP65	
Energy Efficiency Label	A+	
Materials	Housing	PC and ABS
	Cover	Opal PC
Service Lifetime	20'000 hours	
Power Factor	≥ 0.9	
Ingress Protection	IP65	
IK Rating	IK06	
Temperature Range	-20° ... +50°C	
Dimensions (d x h)	Ø 280 x 55 mm	



## ELECTRICAL CHARACTERISTICS

System Power	18W
Input Voltage	220-240V AC
Operating Frequency	50-60 Hz



## LIGHT CHARACTERISTICS

Product Reference	CLSM2818
Luminous Flux	1'500 lm
Luminous Efficiency	83 lm/W
Beam Angle	120°
Colour Temperature (CCT)	3 in 1
CRI	> 80