



CREO Light.
Light years ahead.




**Inground Light
Mini 4.8W 24V IP68**

PRODUCT HIGHLIGHTS

- ~ Recessed fitting for ground installation for outdoor and indoor use
- ~ High brightness LED light with consistent colour temperature and high CRI
- ~ Long service lifetime of 50'000 hours
- ~ Cover made of stainless steel "316L". Body made of anodized aluminium
- ~ Optional: Body made of stainless steel "316"
- ~ External 24V DC constant voltage LED driver required (not included)
- ~ 8 mm tempered glass enables drive over with maximum load of 1'000 Kg
- ~ 4'000K version available upon request. Frosted cover glass is optional
- ~ No UV or IR emissions. No mercury

GENERAL CHARACTERISTICS

Product Name	LD GL MINI 4.8W 24V IP68
Energy Efficiency Label	A
Materials	Body Anodized Aluminium Diffuser Tempered Glass Cover Stainless Steel "316L"
LED Type	CREE™
LED Quantity	3
Average Lifetime	50'000 hours
Start Time from 0% to 100%	0 sec
Mercury Content	0.0 mg
Ingress Protection	IP68
Dimensions (d x h; d1 x h1)	Ø 90 x 52 mm; Ø 68 x 71 mm
Weight	515 g



ELECTRICAL CHARACTERISTICS

System Power	4.8W
Forward Voltage	24V DC

LIGHT CHARACTERISTICS

Product Reference	GL MINI 4.8W/SP/830			GL MINI 4.8W/FL/830			GL MINI 4.8W/WFL/830		
Luminous Flux	380 lm			380 lm			380 lm		
Luminous Intensity	1'981 cd			680 cd			456 cd		
Luminous Efficiency	79 lm/W			79 lm/W			79 lm/W		
Beam Angle	15°			40°			60°		
Colour Name	Warm White			Warm White			Warm White		
Colour Temperature (CCT)	3'000 K			3'000 K			3'000 K		
CRI	83			83			83		
	DISTANCE (m)	CONE DIAMETER (m)	ILLUMINANCE (lx)	DISTANCE (m)	CONE DIAMETER (m)	ILLUMINANCE (lx)	DISTANCE (m)	CONE DIAMETER (m)	ILLUMINANCE (lx)
	2.5	0.83	317	2.5	1.93	48	2.5	2.53	73
	2.0	0.66	495	2.0	1.54	109	2.0	2.02	114
	1.5	0.50	880	1.5	1.16	302	1.5	1.52	203
	1.0	0.33	1'981	1.0	0.77	680	1.0	1.01	456
	0.5	0.17	7'924	0.5	0.39	2'720	0.5	0.51	1'824