



**Inground Light
Nano V2 2W 24V IP68**




PRODUCT HIGHLIGHTS

- ~ Recessed fitting for ground installation for outdoor and indoor use
- ~ High brightness LED light with consistent colour temperature and high CRI
- ~ Long service lifetime of 50'000 hours
- ~ Cover made of stainless steel "316L". Body made of anodized aluminium
- ~ Stainless top cover available
- ~ External 24V DC constant voltage LED driver required (not included)
- ~ 8 mm tempered glass enables drive over with maximum load of 1'000 Kg
- ~ 4'000K version available upon request. Frosted cover glass is optional
- ~ No UV or IR emissions. No mercury



GENERAL CHARACTERISTICS

Product Name	LD GL NANO V2 2W 24V IP68
Energy Efficiency Label	A
Materials	Body Anodized Aluminium Diffuser Tempered Glass Cover Stainless Steel "316L"
LED Type	CREE™
LED Quantity	1
Average Lifetime	50'000 hours
Start Time from 0% to 100%	0 sec
Mercury Content	0.0 mg
Ingress Protection	IP68
Dimensions (d x h; d1 x h1)	Ø 55 x 63 mm; Ø 40 x 84 mm
Weight	215 g



ELECTRICAL CHARACTERISTICS

System Power	2W
Forward Voltage	24V DC



LIGHT CHARACTERISTICS

Product Reference	GL NANO-V2 2W/830
Luminous Flux	15 lm
Luminous Intensity	-
Luminous Efficiency	8 lm/W
Beam Angle	-
Colour Name	Warm White
Colour Temperature (CCT)	3'000 K
CRI	83