


PRODUCT HIGHLIGHTS

- Recessed fitting for ground installation for outdoor and indoor use
- High brightness LED light with consistent colour temperature
- Body made of sand casting stainless steel "316L"
- Long service lifetime of 30'000 hours
- ABS installation housing. 0.5 meter of waterproof cable connector
- No UV or IR emissions. No mercury

GENERAL CHARACTERISTICS

Product Name		LD UL01F 1.5W 24V WW IP68
Energy Efficiency Label		A
Materials B	Body	Sand Casting 316L Stainless Steel
Diff	fuser	Tempered Glass
LED Type		COB
LED Quantity		1
Average Lifetime		30'000 hours
Start Time from 0% to 100%		0 sec
Mercury Content		0.0 mg
Ingress Protection		IP68
IK Rating		IK06
Dimensions (d x h; d1)		Ø 35 x 42 mm; Ø 27 mm
Housing Dim. (d2 x h2; d	d3)	Ø 34 x 83 mm; Ø 50 mm



) ELECTRICAL CHARACTERISTICS

1.5W 24V DC

— LIGHT CHARACTERISTICS

System Power

Input Voltage

Product Reference	UL01F 1.5W/VWFL/830
Luminous Flux	100 lm
Luminous Intensity	67 lm/W
Beam Angle	120°
Colour Name	Warm White
Colour Temperature (CCT)	3'000 K
CRI	> 80