



Inground Light UL0306 3W 230V IP67



## **PRODUCT HIGHLIGHTS**

- Recessed fitting for ground installation for outdoor and indoor
- High brightness LED light with consistent colour temperature
- Cover made of stainless steel "316". Body made of anodized aluminium
- Long service lifetime of 30'000 hours
- No UV or IR emissions. No mercury

## **GENERAL CHARACTERISTICS**

LD UL0306 3W 230V IP67 Product Name

Energy Efficiency Label Α

Materials Body Anodized Aluminium

Diffuser Tempered Glass Cover Stainless Steel "316"

COB

LED Type LED Quantity

Average Lifetime 30'000 hours

Start Time from 0% to 100% 0 sec Mercury Content 0.0 mg Ingress Protection IP67 **IK Rating** IK08

Dimensions ( $d \times h$ ) Ø 63 x 95 mm

Weight 437 g



## **ELECTRICAL CHARACTERISTICS**

System Power

Forward Voltage 220-240V AC



## LIGHT CHARACTERISTICS

Product Reference	UL0306 3W/WFL/830	
Luminous Flux	100 lm	
Luminous Intensity	208 cd	
Luminous Efficiency	33 lm/W	
Beam Angle 40°		
Colour Name	Warm White	
Colour Temperature (CCT)	(CCT) 3'000 K	
CRI	>80	

DISTANCE	CONE DIAMETER	ILLUMINANCE
(m)	(m)	(lx)
2.5	1.93	33
2.0	1.54	52
1.5	1.16	92
1.0	0.77	208
0.5	0.39	832
▼ ·		

