



**Track Light  
TLZ IP20**




## PRODUCT HIGHLIGHTS

- High quality LED Track Light providing symmetric light distribution with maximum efficiency and optimum photometric properties
- LED light engine compliant with ZHAGA interface specification Book 3
- Dimmable with Tridonic™ LCA drivers
- Excellent Colour Rendering Index CRI > 80 (Optional 90, 95, 98)
- Standard CCT: 3'000 K and 4'000 K
- Different beam angle available
- Compatible with EU standard tracks from Global, Stucchi
- Long service lifetime of 50'000 hours (L80F10)
- Available in white or matt black

## GENERAL CHARACTERISTICS

Product Name	TLZ
Energy Efficiency Label	A+
Materials:	Housing Aluminium Reflector Aluminium
LED Brand	TRIDONIC™
LED Type	COB (G7-17)
LED Quantity	1 Module
Service Lifetime	50'000 hours
Ingress Protection	IP20



## ELECTRICAL & PHOTOMETRIC CHARACTERISTICS

Product reference	RATED POWER	FORWARD CURRENT	OPERATING FREQUENCY	BEAM ANGLE	CCT	CRI	LUMINOUS FLUX (lm)	LUMINOUS EFFICIENCY (lm/W)	DIAMETER (d) (mm)	HEIGHT (h) (mm)	HEIGHT (h1) (mm)
TLZ1108WF830B	25 W	700 mA	50-60 Hz	36°	3'000 K	> 80	3'730	149	Ø 85	110	120
TLZ1108WF840B	25 W	700 mA	50-60 Hz	36°	4'000 K	> 80	3'845	154	Ø 85	110	120
TLZ1310WF830B	37 W	1'050 mA	50-60 Hz	36°	3'000 K	> 80	5'690	154	Ø 106	130	152
TLZ1310WF840B	37 W	1'050 mA	50-60 Hz	36°	4'000 K	> 80	5'930	160	Ø 106	130	152
TLZ1511WF830B	49 W	1'400 mA	50-60 Hz	36°	3'000 K	> 80	7'710	157	Ø 110	150	167
TLZ1511WF840B	49 W	1'400 mA	50-60 Hz	36°	4'000 K	> 80	8'040	164	Ø 110	150	167