



**LED Floodlight
FL121683065 15W 230V
IP65**




PRODUCT HIGHLIGHTS

- ~ Projector Light for outdoor use
- ~ Aluminum housing with tempered front glass
- ~ SMD LED Design to maximize product reliability
- ~ Built-in fixed output driver
- ~ High system efficiency up to 93 lm/W
- ~ High colour consistency. Excellent CRI. Standard: CRI>80
- ~ Symmetric light distribution with optimum photometric properties
- ~ Colour temperature: 3'000K. Available upon request: 4'000K and 6'000K

GENERAL CHARACTERISTICS

Product Name	LED Floodlight FL121683065 15W 230V IP65	
Energy Efficiency Label	A+	
Materials	Housing	Aluminum
	Cover	Tempered glass
Led Type	SMD	
Temperature Range	-20°C ...+50°C	
Ingress Protection	IP65	
Dimensions (l x h x w; b)	115 x 161 x 110 mm; 139 mm	



ELECTRICAL CHARACTERISTICS

System Power	15W
Voltage	220-240V AC
Main Frequency	50-60 Hz

LIGHT CHARACTERISTICS

Product Reference	FL121683065
Luminous Flux	1'400 lm
Luminous Efficiency	93 lm/W
Colour Name	Warm White
Colour Temperature (CCT)	3'000 K
CRI	> 80